



CALCULATIONS FOR CONVEYING SCREWS

1. Calculation of the flow rate

$$\dot{V} = A s n \varphi c \quad \left[\frac{\text{m}^3}{\text{h}} \right]$$

$$A = \frac{\pi D^2}{4} \quad \text{Screw cross-section}$$

D = Outside screw diameter

The reduction of the cross-section by the screw shaft is negligible.

$$S = (0.5 \dots 1.0) D$$

Screw pitch;

Lower values for s with a large screw diameter D.

n = Speed of the screw shaft

φ = 0.15 ... 0.45 Filling level; higher values with free-flowing conveyed material with low friction.

c = coefficient of velocity; it takes into account the leaving behind of the conveyed material with respect to the screw analogous to the trough chain conveyor.

$c \approx 1$ with full screws

$c \approx 0.8 \dots 0.9$ for conveyor screws

$c \approx 0.5 \dots 0.8$: with segment screws

When conveying increases, the quantity of the conveyed material decreases by approx. 2% per 1° pitch angles, this applies for pitch angle δ to approximately 20°. If the pitch is greater or in vertical conveyors, the volume of conveyed material decreases to a higher degree depending on the type of material.

Precise · Fast
Inexpensive

www.schneckenfluegel.de



2. Drive capacity

$$P_N = \frac{m \cdot g (l \cdot f_{\text{tot}} + h)}{\eta} \quad \left[\frac{\text{Kg m}^2}{\text{s}^3} = 1\text{W} \right]$$

l Conveying length

f_{tot} Displacement resistance (2 – 4 horizontal screw conveyors)
(4 – 8 vertical conveyors)

h Height difference between material infeed and discharge

$\eta \approx 0.8$ capacity reduction factor

The frictional power due to the inherent weight of the conveyor can therefore be ignored due to its low influence.

3. Axial force of the screw shaft

$$F_a = \frac{M_t}{\frac{D_m}{2} \tan(\alpha + \rho)} \quad [\text{N}]$$

$M_t = \eta \frac{P_N}{\omega}$ Torque at the screw shaft

P_N and η see above

ω Rotational frequency of the screw shaft

$D_m \approx \frac{D}{2}$ Average screw diameter

D Outside screw diameter

α Pitch angle of the screw: relate α to D_m

ρ Frictional angle between the conveyed product and the screw

The axial force of the screw shaft is necessary for specification of the axial bearing; the bearings are only radially subjected to strain by the inherent weight of the screw shaft, the material load is negligible.

Precise · Fast
Inexpensive
www.schneckenfluegel.de



DESIGN – U-trough screws in compliance with DIN 15261

The values in the table below refer to conventional, free-flowing conveyed materials. These conveyed materials are divided into three classes:

Class A

Free-flowing, light, non-abrasive conveyed material, such as raw flour, mixed feed, grain, beans etc.

Class B

Not quite free-flowing conveyed material with higher bulk density, somewhat abrasive or fine-grained or small-sized materials, such as sugar, sawdust, lime, salts, fertilisers, etc.

Class C

Very abrasive, viscous, fibrous or coarse-grained conveyed material with negative flow properties such as sand, ash, cement, limestone etc.

Displacement resistance up to 2.0

Conveying velocity

V = approx. 0.3 – 0.5 m/s

Filling level 0.4 – 0.5

Displacement resistance up to 3.5

Conveying velocity

V = approx. 0.2 – 0.3 m/s

Filling level 0.3

Displacement resistance up to 5.0

Conveying velocity

V = approx. 0.1 m/s

Filling level 0.3

SCREWS				MATERIAL CLASSES					
				Conveying capacity and speed					
Ø	Pitch	Tubular shaft	Surface	A		B		C	
mm	mm	Ø	m ²	α = 45%	n = Ump	α = 30%	n = Ump	α = 15%	n = Ump
m ³ /h				m ³ /h		m ³ /h		m ³ /h	
100	100	35	0.007	2.6	140	1.4	112	0.5	90
125	125	35	0.011	5.4	125	2.8	100	1.1	80
160	160	44.5	0.018	9.0	112	4.8	90	1.8	71
200	200	51	0.029	15.5	100	8.4	80	3.4	63
250	250	57	0.045	27	90	15	71	5.8	56
315	300	63	0.073	47	80	25	63	10	50
400	350	76	0.121	80	71	42	56	17	45
500	400	108	0.167	127	63	67	50	27	40
630	450	133	0.302	180	50	96	40	38	32
800	500	159	0.555	260	40	138	32	54	25
1000	560	191	0.755	360	32	190	25	76	20
1250	630	216	1.200	500	25	270	20	110	16

The conveying velocity must be determined on the basis of the type and properties of the material.

Precise · Fast
Inexpensive
www.schneckenfluegel.de



MATERIALS SUITABLE FOR TRANSPORT WITH CONVEYING SCREWS

Conveyed material	Bulk density t/m³	Material class ABC	Shifting resistance f_{tot}
Aluminium hydrate	0.21-0.23	B	3.4
Ammonium saltpetre	1.0	C	4.0
Apples, dried, pressed	0.24	B	3.4
Asbestos	2.2-2.8	C	4.0
Arsenic oxide	1.6-1.9	B	3.4
Ash, dry, wet	0.7	C	5.5
Orange peel, dry	0.24	B	4.0
Activated carbon	0.2	B	3.0
Waste water sludge	0.8	B	2.8
Alkali cellulose	0.25	C	4.0
Baking powder	0.9	C	2.8
Cotton seeds, chopped	0.4	A	2.3
Cotton press cake	0.35	A	2.3
Cotton leaves	0.3	A	2.3
Cotton husks	0.2	A	2.3
Cotton seeds	0.4	A	2.3
Cotton seed meal	0.3	B	3.4
Lead salt, arsenic-acidic	1.1	B	3.4
Borax	0.8	B	3.8
Malting barley, dry	0.4-0.47	B	2.0
Malting barley, wet	0.9-0.95	B	2.3
Brown iron ore	3.2	C	5.0
Lignite, dry	0.65	B	3.0
Buckwheat	0.6	B	2.3
Cellophane flakes	0.46	A	2.3
Cement (Portland)	1.6	C	3.0
Powdered egg	0.25	B	3.4
Peanuts, shelled	0.64	B	2.0
Peanuts, crushed	0.65	A	2.3
Acetic acid salt	0.29	B	3.4
Ore, fine	2.8	C	3.48
Ore, granules	2.4	C	5.0
Ore, coarse	2.2	C	5.0
Earth, loamy	1.8	B	3.4
Earth, dry	1.5	B	4.0
Flaxseed	0.72	A	1.8
Flax, crushed	0.8	B	2.8
Fly ash	0.8-1.2	C	5.0
Fish meal	0.9	A	2.3
Barley	0.8	A	2.3
Face powder	0.4-0.5	B	3.4
Glauber's salt	1.4	B	3.4
Mica, ground	0.25	B	3.4
Graphite, flaky	0.65	A	2.3
Graphite powder	0.35	A	2.0
Gypsum, crushed	1.0-1.5	C	4.0
Gypsum, ground, dry	0.8-1.0	B	2.8
Semolina	0.66	A	2.3
Oats, crushed	0.35	A	2.3
Oats, rolled	0.3	A	2.3
Oats, loose	0.5	A	2.0
Hops, dry	0.56	B	2.3
Hops, wet	0.85	B	2.0
Charcoal, hard	0.33	A	2.0
Charcoal, soft	0.4	A	2.3
Wood flour	0.25-0.6	B	1.8
Coffee, green	0.51	A	2.3
Coffee, ground	0.4	A	2.0
Coffee, roasted	0.4	A	2.3
Chalk powder	2.0	C	3.0
Lime, slaked	0.55	A	2.3

Conveyed material	Bulk density t/m³	Material class ABC	Shifting resistance f_{tot}
Lime hydrates	0.5	B	2.5
Calcium, arsenic-acidic	0.67	B	2.8
Cocoa beans with husk	0.6	C	2.0
Cocoa beans without husk	0.55	C	2.0
Cocoa nuts, roughly ground	0.3-0.35	A	2.0
Potassium salt	0.9	C	3.5
Bran	0.25	A	2.5
Coal, dry, lump coal	0.83	C	3.5
Coal, dry, cob coal	0.9	B	3.0
Coal, dry, lignite	0.65	B	3.0
Coal dust	0.8	A	2.3
Cork, ground	0.8	B	3.8
Cork, crushed	0.7	C	3.8
Wood resin, synth. alcohol	0.8	B	2.8
Chalk	1.1	B	3.4
Copra, cake	0.45	A	2.3
Cobra, broken	0.65	A	2.3
Copra, powder	0.65	A	2.3
Gravel, dry	1.3	C	5.0
Gravel, moist	1.5	C	5.0
Potatoes	0.7	A	2.5
Linseed, crushed	0.5	A	2.0
Almonds	0.45	B	2.0
Malt, dry, whole	0.45	A	2.0
Malt, dry, ground	0.35	A	2.3
Malt, wet	0.6	B	2.3
Maize, coarsely ground	0.6	A	2.0
Magnesia, fired	0.25	B	2.4
Flour	0.6	A	2.3
Milk powder	0.45	A	2.0
Mixed feed	0.5	A	2.3
Na ₂ CO ₃	0.9	C	3.0
Oilseed	0.7	A	2.3
Crushed oilseed	0.5	B	3.4
Phosphoric salts	0.7	B	3.8
Rice, polished	0.75	A	2.0
Rice, raw	0.56	A	2.0
Rye	0.74	A	2.0
Castor oil bean	0.4	A	2.0
Sawdust	0.21	B	2.8
Salt, dry	1.1	B	3.0
Soap powder	0.6	B	2.5
Soda, light	0.4	C	4.0
Soda, heavy	0.9	C	3.4
Sludge	0.67	C	3.5
Sulphur, broken	0.9	C	3.5
Starch, pulverised	0.7	A	2.8
Sand, dry	1.8	C	5.0
Soya beans, pressed	0.64	A	2.3
Soya beans, broken	0.55	A	2.3
Soya beans, raw	0.41	A	2.3
Soy bean flour	0.43	A	2.3
Soy bean meal	0.64	B	2.3
Lump coal	0.83	B	3.5
Coal tar	0.72	B	2.8
Tobacco, dry	0.2	A	2.8
Talcum	0.9	B	2.8
Talcum powder	0.9	B	2.8